

# EYELINER PIGMENTS

## MSDS

# *A Permanent Solution*



### **IMPORTANT NOTE:**

Glycerin, Alcohol and Water are ingredients in all our pigment formulas. Those specs can be found on our site at [www.apermanentsolution.com](http://www.apermanentsolution.com) , in separate documents.



# Material Safety Data Sheet

Pigment Ink

TN-1

Indigo Black

---

## 1. Product and Company Identification

Product Name: Pigment Ink  
Product Code: TN-1  
Company: A Permanent Solution  
1038 E. Bastanchury Road #186  
Fullerton, CA 92835 USA  
www.apermanentsolution.com E-mail: info@apermanentsolution.com  
Phone: (714) 441-1900 Fax: (714) 441-1808

---

## 2. Hazards Identification

Physical State: Solid  
OSHA/HCS Status: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of the product.  
Emergency Overview: No specific hazard.  
NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED.  
No known significant effects or critical hazards. Avoid prolonged contact with eyes, skin and clothing.  
Routes of Entry: Absorbed through skin. Eye contact. Inhalation. Ingestion.  
Potential acute health effects:  
Eyes: This product may irritate eyes upon contact.  
Skin: No known significant effects or critical hazards.  
Inhalation: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.  
Ingestion: No known significant effects or critical hazards.

---

## 3. Composition/Information on Ingredients

There are no additional ingredients which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Pigment Ink

TN-1

Indigo Black

1

---

#### 4. First Aid Measures

Eye Contact:	Affected individual should remove contact lenses, if present. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if irritation occurs.
Skin Contact:	Wash skin with soap and water. Get medical attention if irritation develops.
Inhalation:	Move to fresh air. Get medical attention if irregular breathing occurs.
Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

---

#### 5. Fire-Fighting Measures

Products of Combustion:	Decomposition products may include the following materials: metal oxide(s)
Fire-Fighting media and Instructions:	Use an extinguishing agent for the surrounding fire.
Special protective equipment for fire-fighters:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

---

#### 6. Accidental Release Measures

Personal Precautions:	Keep unnecessary personnel away. Provide adequate ventilation. Use suitable protective equipment (section 8).
Environmental Precautions:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for Cleaning Up:	If emergency personnel are unavailable, carefully scoop up spilled materials and use a non-sparking or explosion proof means to transfer to an appropriated container for disposal by incineration. Avoid creating dusty conditions and prevent wind dispersal.

---

#### 7. Handling and Storage

Handling:	Avoid breathing dust.
Storage:	Keep container tightly closed. Store in a dry, cool and well-ventilated area. Store in accordance with local regulations.

Pigment Ink

TN-1

Indigo Black

2

---

#### 8. Exposure Controls/Personal Protection

<b>Engineering Measures:</b>	No special ventilation required. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
<b>Environmental Exposure Controls:</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with requirements or environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
<b><u>Personal Protection:</u></b>	
<b>Eyes:</b>	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
<b>Skin:</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory:</b>	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
<b>Hands:</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

## 9. Physical and Chemical Properties

<b>Physical State:</b>	Solid
<b>Appearance:</b>	Black Powder
<b>Flash Point:</b>	Closed cup: 500°C (932°F)

## 10. Stability and Reactivity

<b>Stability:</b>	The product is stable.
<b>Hazardous Polymerization:</b>	Will not occur.
<b>Hazardous Decomposition Products:</b>	Under normal conditions of storage and use, hazardous decomposition should not be produced.

Pigment Ink

TN-1

Indigo Black

3

## 11. Toxicological Information

Chronic Effects: No known toxic effects on humans. No known effects or critical hazards. Avoid prolonged contact with eyes, skin and clothing.

Mutagenicity/Teratogenicity: No known significant effects or critical hazards.

Reproductive Toxicity: No known significant effects or critical hazards.

---

## 12. Ecological Information

Environmental Effects: No known significant effects or hazards.

---

## 13. Disposal Considerations

Waste Disposal: The generation of waste should be avoided or minimized whenever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## 14. Transport Information

DOT Classification: Not classified as dangerous.

---

## 15. Regulatory Information

OSHA/HCS Status: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the products. This MSDS should be retained and available for employees and other users of this product.

WHMIS (Canada): Not controlled under WHMIS (Canada).

Europe: This product is not classified according to EU legislation.

Pigment Ink                      TN-1                      Indigo Black    4

---

## 16. Other Information

Hazardous Materials Information System (USA):  
Health: 1

**Flammability:** 1  
**Physical Hazards:** 0  
**Personal Protection:** B

**National Fire Protection Association (USA):**

**Health:** 1  
**Flammability:** 1  
**Instability:** 0

**Date of Revision:** November 8, 2012



# Material Safety Data Sheet

Pigment Ink

TN-3

Brown Velvet

---

## 17. Product and Company Identification

Product Name: Pigment Ink  
Product Code: TN-3  
Company: A Permanent Solution  
1038 E. Bastanchury Road #186  
Fullerton, CA 92835 USA  
www.apermanentsolution.com E-mail: info@apermanentsolution.com  
Phone: (714) 441-1900 Fax: (714) 441-1808

## 18. Hazards Identification

Physical State: Solid.  
OSHA/HCS status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
Emergency Overview: No specific hazard.  
MAY CAUSE EYES AND SKIN IRRITATION. CANCER HAZARD-CONTAINS MATERIAL WHICH CAN CAUSE CANCER.  
Slightly irritating to the eyes and skin. Avoid exposure-obtain special instructions before use. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure. Wash thoroughly after handling.  
Potential acute health effects:  
Eyes: Slightly irritating to the eyes. This product may irritate eyes upon contact.  
Skin: Slightly irritating to the skin.  
Inhalation: Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.  
Ingestion: No known significant effects or critical hazards.

---

## 19. Composition/Information on Ingredients

Iron Oxide Red C.A.S # 1309-37-1  
Talc C.A.S. # 14807-96-6  
Barium Sulfate C.A.S. # 7727-43-7

---

Pigment Ink

TN-3

Brown Velvet

1

---

Magnesite C.A.S. # 546-93-0  
Crystalline Silica, Quartz C.A.S. # 14808-60-7  
Kaolin Clay C.A.S. # 1332-58-7

There are no additional ingredients which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

---

## 20. First Aid Measures

Eye Contact:	Remove contact lenses if present. Thoroughly flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact:	Wash skin with soap and water. Get medical attention if irritation develops.
Inhalation:	Move to fresh air. Get medical attention if irregular breathing occurs.
Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

---

## 21. Fire-Fighting Measures

Products of Combustion:	Decomposition products may include the following materials: Carbon dioxide, carbon monoxide, sulfure oxides, metal oxide(s)
Fire-Fighting media and Instructions:	Use an extinguishing agent for the surrounding fire.
Special protective equipment for fire-fighters:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

---

## 22. Accidental Release Measures

Personal Precautions:	Keep unnecessary personnel away. Provide adequate ventilation. Use suitable protective equipment (section 8).
Environmental Precautions:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for Cleaning Up:	If emergency personnel are unavailable, carefully scoop up spilled materials and use a non-sparking or explosion proof means to transfer to an appropriated container for disposal by incineration. Avoid creating dusty conditions and prevent wind dispersal.

---

Pigment Ink

TN-3

Brown Velvet

2

---

## 23. Handling and Storage

Handling:	Do not get in eyes or on skin or clothing. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Avoid breathing dust.
Storage:	Keep container tightly closed. Store in a dry, cool and well-ventilated area. Store in accordance with local regulations.

## 24. Exposure Controls/Personal Protection

Engineering Measures:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.	
Environmental Exposure Controls:	Emissions from ventilation or work process equipment should be checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
Personal Protection:	Safety glasses should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates this is necessary.	
Exposure Limits:	Iron Oxide Red	<p>NIOSH REL (United States, 6/2009).  TWA: 5 mg/m<sup>3</sup>, (as Fe) 10 hour(s). Form: Dust and fumes  OSHA PEL 1989 (United States, 3/1989).  STEL: 10 ppm, (as Fe) 15 minutes(s). Form: Total particulates  ACGIH TLV (United States, 1/2011).  TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  OSHA PEL 1989 (United States, 3/1989).  TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Total dust  OSHA PEL (United States, 6/2010).  TWA: 10 mg/m<sup>3</sup> 8 hour(s).</p>
	Talc	<p>OSHA PEL 1989 (United States, 3/1989).  TWA: 2 mg/m<sup>3</sup> 8 hour(s). Form: Respirable dust  NIOSH REL (United States, 6/2009).  TWA: 2 mg/m<sup>3</sup> 10 hour(s). Form: Respirable fraction  ACGIH TLV (United States, 1/2011).  TWA: 01 f/cc 8 hour(s).  OSHA PEL Z3 (United States, 9/2005).  STEL: 1 f/cc 30 minute(s). Form: not containing asbestos  TWA: 20 mppcf 8 hour(s). Form: not containing asbestos  TWA: 0.1 f/cc 8 hour(s).  STEL: 1 f/cc 30 minute(s).</p>

	<p>TWA: 5 mg/m<sup>3</sup> 10 hour(s). Form: Respirable fraction  TWA: 10 mg/m<sup>3</sup> 10 hour(s). Form: Total dust  OSHA PEL (United States, 6/2010).  TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  TWA: 15 mg/m<sup>3</sup> 8 hour(s). Form: Total dust  NIOSH REL (United States, 6/2009).  TWA: 5 mg/m<sup>3</sup> 10 hour(s). Form: Respirable fraction  TWA: 10 mg/m<sup>3</sup> 10 hour(s). Form: Total dust  OSHA PEL (United States, 6/2010).  TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  TWA: 15 mg/m<sup>3</sup> 8 hour(s). Form: Total dust  OSHA PEL 1989 (United States, 3/1989).  TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  TWA: 15 mg/m<sup>3</sup> 8 hour(s). Form: Total dust  OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO<sub>2</sub>+2)  TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Respirable  OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO<sub>2</sub>+5)  TWA: 250 mppcf 8 hour(s). Form: Respirable  OSHA PEL 1989 (United States, 3/1989).  TWA: 0.1 mg/m<sup>3</sup>, (as quartz) 8 hour(s). Form: Respirable dust  ACGIH TLV (United States, 1/2011).  TWA: 0.025 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  NIOSH REL (United States, 6/2009).  TWA: 0.05 mg/m<sup>3</sup> 10 hour(s). Form: Respirable dust  OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO<sub>2</sub>+2)  TWA: 30 mg/m<sup>3</sup> 8 hour(s). Form: Total dust  ACGIH TLV (United States, 1/2011).  TWA: 2 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  OSHA PEL 1989 (United States, 3/1989).  TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Total dust  OSHA PEL 1989 (United States, 3/1989).  TWA: 0.1 mg/m<sup>3</sup>, (as quartz) 8 hour(s). Form: Respirable dust  NIOSH REL (United States, 6/2009).  TWA: 5 mg/m<sup>3</sup> 10 hour(s). Form: Respirable fraction  TWA: 10 mg/m<sup>3</sup> 10 hour(s). Form: Total dust  OSHA PEL (United States, 6/2010).  TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction  TWA: 15 mg/m<sup>3</sup> 8 hour(s). Form: Total dust</p>
Magnesite	
Crystalline Silica, Quartz	
Kaolin Clay	

## 25. Physical and Chemical Properties

Physical State:	Solid
Appearance:	Brown Powder
Flash Point:	Closed cup: 500°C (932°F)

## 26. Stability and Reactivity

Stability:	The product is stable.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition should not be produced.

Pigment Ink

TN-3

Brown Velvet

4

## 27. Toxicological Information

Chronic Effects:	Iron Oxide Red	ACGIH = A4	IARC = 3		
	Talc	ACGIH = A1	IARC = 1		
	Crystalline Silica	ACGIH = A2	IARC = 1	NIOSH = +	NTP=PROVEN.
	Kaolin Clay	ACGIH = A4			

Slightly irritating to the eyes and skin. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure. Wash thoroughly after handling.

Mutagenicity/Teratogenicity: No known significant effects or critical hazards.

Reproductive Toxicity: No known significant effects or critical hazards.

## 28. Ecological Information

Environmental Effects: No known significant effects or hazards.

Aquatic Ecotoxicity:	Barium Sulfate	Result: Acute EC50 32000 ug/L Fresh water Species: Daphnia-water flea-Daphnia magna Exposure: 48 hours
----------------------	----------------	--

## 29. Disposal Considerations

Waste Disposal:	The generation of waste should be avoided or minimized whenever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-----------------	--

## 30. Transport Information

DOT Classification: Refer to the bill of lading for proper shipping information.

Pigment Ink	TN-3	Brown Velvet	5
-------------	------	--------------	---

## 31. Regulatory Information

OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

WHMIS (Canada): Class D-2A: Material causing other toxic effects.

Europe:

This product is not classified according to EU legislation.

---

## 32. Other Information

### Hazardous Materials Information System (USA):

Health: 1  
Flammability: 1  
Physical Hazards: 1  
Personal Protection: B

### National Fire Protection Association (USA):

Health: 1  
Flammability: 1  
Instability: 1

Date of Revision: May 31, 2012



**Ingestion:** Do not give anything by mouth to an unconscious person. Do not induce vomiting. Get immediate medical attention.

---

### 37. Fire Fighting Measures

Nonflammable organic pigment products.

**Extinguishing Media:** Carbon dioxide, dry chemical or foam recommended. Apply water spray to cool exposed closed containers.

**Special Fire-Fighting Procedures:** Self-contained breathing apparatus (SCBA) and full protective equipment recommended.

**Unusual Fire and Explosion Hazards:** Fire or excessive heat may produce hazardous decomposition products.

**General Hazard:** Improper handling of any finely divided organic pigment powder may lead to dust cloud formation which may be an explosion hazard.

**Flammability Data:**

<b>Flash Point:</b>	Non-flammable material		
<b>Flammability Limits:</b>	Not applicable		
<b>Autoignition Temperature:</b>	Not applicable		
<b>Dust Cloud Ignition Temperature:</b>	640°F		
<b>Dust Layer Ignition Temperature:</b>	1210°F		

**NFPA Ratings:** Health: 1      Flammability: 1      Reactivity: 0

**HMIS Ratings:** Health: 1      Flammability: 1      Reactivity: 0

---

### 38. Accidental Release Measures

**Small Spill:** For dry powder spills, inert materials such as sand may be added to control dusting prior to cleanup. Industrial grade vacuum sweepers are also recommended. Place spilled material into appropriate waste containers for disposal.

**Large Spill:** Contain spilled material immediately with an inert substance such as sand or earth. Use plastic or aluminum shovel to transfer diluted waste material into appropriate containers for disposal.

Airborne organic pigment dust may be an explosion hazard. Secure possible sources of ignition and avoid dusting.

---

### 39. Handling and Storage

**Handling:** Avoid employee exposure through the use of appropriate engineering controls and good industrial hygiene practices.

**Storage:** Store in a moderately cool, dry, well-ventilated area away from direct sources of heat. Empty containers may contain product residues and should be handled appropriately. Position containers so that any labeling information is visible.

---

## 40. Exposure Controls and Personal Protection

Engineering Controls:	The use of local exhaust ventilation is recommended.
Personal Protection:	NIOSH approved dust respirators are recommended when handling in areas of pigment dusting. Safety glasses are also recommended. Impervious clothing should be worn when gross contact is likely, such as when cleaning up spills of large amounts.
Exposure Limits:	There are no ACGIH TLV's or OSHA PEL's established for this product.

The OSHA PEL for nuisance dust is 15 mg/m<sup>3</sup> (total dust), and 5 mg/m<sup>3</sup> (respirable dust) recommended. The recommended ACGIH TLV for nuisance dust is 10 mg/m<sup>3</sup>.

---

## 41. Physical and Chemical Properties

Appearance:	Finely divided powder
Color:	Green
Melting Point:	Undetermined
Specific Gravity:	17.61 lbs/gal
Percent Volatile:	Negligible
Vapor Pressure:	Not applicable
Boiling Point:	Unknown
Molecular Formula:	C <sub>32</sub> HC <sub>15</sub> CuN <sub>8</sub>
Volatile Organic Compounds:	None

---

## 42. Stability and Reactivity

General:	This product is a stable compound and hazardous polymerization will not occur.
Incompatibility:	Avoid strong oxidizing agents such as peroxides, chlorates, perchlorates, nitrates, and permanganates. Oxidizing materials may vigorously evolve oxygen in large amounts.
Hazardous Decomposition Products:	When involved in a fire, burning organic pigments may evolve noxious gases which are toxic. These compounds may include carbon monoxide, carbon dioxide, nitrous oxides, or hydrogen chloride, depending on the pigment type.

---

## 43. Toxicological Information

General:	Based upon industry-wide experience over many years of manufacturing and published toxicological studies, organic pigments in general are considered to be practically non-toxic. This low order of toxicity is probably due to the fact that pigments are somewhat inert and insoluble substances. There are no established TLV's or PEL's for this product.
----------	---

---

Pigment Ink	TN-7	Jungle Green	3
-------------	------	--------------	---

---

Acute Toxicity:	This product has a reported acute oral LD <sub>50</sub> value of 5 gm/kg or greater in rats. Skin and eye irritation studies have been reported to be negative. An
-----------------	--

**Chronic Toxicity:** aquatic toxicity study on water fleas and bluegill fish indicated that Pigment Green 7 did not constitute a significant hazard in the aquatic environment. There was no evidence of absorption or adverse health effects based upon a 90-day feeding study in rats and mice. Pigment Green 7 was dropped from the 2-year NTP bioassay program.

**Mutagenicity:** In vitro screening tests for mutagenicity had reported negative results in an Ames Salmonella culture with DMSO solutions or dispersions of commercial pigments.

---

#### 44. Ecological Information

This product has not been evaluated for its ecotoxicity. However, the biodegradation of organic colorants under aerobic conditions is expected to be poor and there is no evidence to suggest they create any significant ecological problems when released into the environment. Since organic pigments are generally insoluble compounds, they are believed to have minimal bioaccumulation and bioavailability characteristics.

---

#### 45. Disposal Considerations

**General:** This product must be disposed of in accordance with all applicable federal, state and local regulations.

**Waste Management:** Incineration or landfilling are recommended disposal techniques. Contact the state or local environmental agency for specific rules. This product is not identified as a RCRA hazardous waste under 40 CFR 261, and is not regulated under CERCLA (Superfund).

---

#### 46. Transport Information

DOT Shipping Name:	Not Regulated
DOT Hazard Class:	None
DOT Label:	None
DOT Placard:	None
Bill of Lading Description:	Pigments NOI Dry

---

#### 47. Regulatory Information

**OSHA Hazard Communication Standard Status:** This product is not considered to be a hazardous substance under OSHA's Federal Hazard Communication Standard 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA) Status:** All of the ingredients of this material have been reported to the US EPA and are included in the TSCA chemical inventory.

---

Pigment Ink	TN-7	Jungle Green	4
-------------	------	--------------	---

---

#### 48. Other Information

Revision Date:

03/11/97



# Material Safety Data Sheet

Pigment Ink

TN-12

Whitest White

---

## 49. Product and Company Identification

Product Name:	Pigment Ink
Product Code:	TN-12
Company:	A Permanent Solution 1038 E. Bastanchury Road #186 Fullerton, CA 92835 USA www.apermanentsolution.com E-mail: info@apermanentsolution.com Phone: (714) 441-1900 Fax: (714) 441-1808

---

## 50. Hazards Identification

Physical State:	Solid.
OSHA/HCS Status:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency Overview:	No specific hazard. <b>MAY CAUSE SKIN AND EYE IRRITATION.</b> Slightly irritating to the eyes and skin. Avoid exposure-obtain special instructions before use. Do not breathe vapor or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.
Potential acute health effects:	
Eyes:	Slightly irritating to the eyes. This product may irritate eyes upon contact.
Skin:	Slightly irritating to the skin.
Inhalation:	Exposure to airborne concentrations above statutory or recommended exposure limits may cause irritation of the nose, throat and lungs.
Ingestion:	No known significant effects or critical hazards.
Other special considerations:	Titanium dioxide has been characterized by IARC as possible carcinogenic to humans (Group 2B) through inhalation (not ingestion). This classification is based upon animal inhalation studies. Epidemiology studies do not suggest as increased risk of cancer in humans from occupational exposure to titanium dioxide.

---

Pigment Ink

TN-12

Whitest White

1

## 51. Composition/Information on Ingredients

Titanium Dioxide C.A.S # 13463-67-7

Amorphous Silicia C.A.S. # 7631-86-9

Aluminum Hydroxide C.A.S. # 21645-51-2

There are no additional ingredients which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

---

## 52. First Aid Measures

Eye Contact:	Remove contact lenses if present. Thoroughly flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact:	Wash skin with soap and water. Get medical attention if irritation develops.
Inhalation:	Move to fresh air. Get medical attention if irregular breathing occurs.
Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

---

## 53. Fire-Fighting Measures

Products of combustion:	Decomposition products may include the following materials: metal oxide(s).
Fire-Fighting media and Instructions:	Use an extinguishing agent for the surrounding fire.
Special protective equipment for fire-fighters:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

---

## 54. Accidental Release Measures

Personal Precautions:	Keep unnecessary personnel away. Provide adequate ventilation. Use suitable protective equipment (section 8).
Environmental Precautions:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for Cleaning Up:	If emergency personnel are unavailable, carefully scoop up spilled materials and use a non-sparking or explosion-proof means to transfer material to an appropriate container for disposal by incineration. Avoid creating dusty conditions and prevent wind dispersal.

---

Pigment Ink

TN-12

Whitest White

2

---

## 55. Handling and Storage

<b>Handling:</b>	Do not get in eyes or on skin or clothing. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Avoid breathing dust.
<b>Storage:</b>	Keep container tightly closed. Store in a dry, cool and well-ventilated area. Store away from incompatible materials. Store in accordance with local regulations.

## 56. Exposure Controls/Personal Protection

<b>Engineering Measures:</b>	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory levels.
<b>Particle Size Considerations:</b>	titanium dioxide: Fine particles are respirable particles with a primary particle diameter of at least 100 nm. Ultrafine particles are respirable particles with a primary particle diameter of less than 100 nm. The grade of titanium dioxide used as a component in this product is not manufactured to contain ultrafine particles as defined above.
<b>Environmental Exposure Controls:</b>	Emissions from ventilation or work process equipment should be checked to ensure they comply with requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Personal Protection:

<b>Eyes:</b>	Safety glasses should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
<b>Skin:</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory:</b>	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
<b>Hands:</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

<b>Exposure Limits:</b>	Titanium Dioxide	OSHA PEL (United States, 6/2010). TWA: 15 mg/m <sup>3</sup> 8 hour(s). Form: Total dust OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m <sup>3</sup> 8 hour(s). Form: Total dust ACGIH TLV (United States, 1/2011). TWA: 10 mg/m <sup>3</sup> 8 hour(s).
	Amorphous Silica	NIOSH REL (United States, 6/2009). TWA: 6 mg/m <sup>3</sup> 10 hour(s).
	Titanium Dioxide	OSHA PEL 1989 (United States, 3/1989). TWA: 2 mg/m <sup>3</sup> , (as Al) 8 hour(s). NIOSH REL (United States, 6/2009). TWA: 2 mg/m <sup>3</sup> , (as Al) 10 hour(s).

Pigment Ink

TN-12

Whitest White

3

## 57. Physical and Chemical Properties

<b>Physical State:</b>	Solid
------------------------	-------

Appearance: White Powder  
Flash Point: Closed cup: 500°C (932°F)

---

## 58. Stability and Reactivity

Stability: The product is stable.  
Hazardous Polymerization: Will not occur.  
Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition should not be produced.

---

## 59. Toxicological Information

Chronic Effects: Titanium Dioxide ACGIH = A4 IARC = 2B NIOSH = +  
Amorphous Silica IARC = 3  
Titanium Dioxide has been characterized by IARC as possible carcinogenic to humans (Group 2B) through inhalation (not ingestion). This classification is based upon animal inhalation studies. Epidemiology studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. It has not been characterized as a potential carcinogen by either NTP or OSHA. Additionally, the Joint Evaluation Committee on Food Additives (JECFA) has reviewed the safety of titanium dioxide finding no problems for its use in food applications and establishing an acceptable daily intake (ADI) for safe use.

Slightly irritating to the eyes and skin. Avoid exposure-obtain special instructions before use. Do not breathe vapor or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Mutagenicity/Teratogenicity: No known significant effects or critical hazards.  
Reproductive Toxicity: No known significant effects or critical hazards.

---

## 60. Ecological Information

Environmental Effects: No known significant effects or hazards.  
Aquatic Ecotoxicity: Slightly toxic to aquatic life.

---

Pigment Ink                      TN-12                      Whitest White                      4

---

## 61. Disposal Considerations

Waste Disposal: The generation of waste should be avoided or minimized whenever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal

contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## 62. Transport Information

DOT Classification: Refer to the bill of lading for proper shipping information.

---

## 63. Regulatory Information

OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
WHMIS (Canada): Class D-2A: Material causing other toxic effects.  
Europe: This product is not classified according to EU legislation.

---

## 64. Other Information

### Hazardous Materials Information System (USA):

Health: 1  
Flammability: 0  
Physical Hazards: 0  
Personal Protection: B

### National Fire Protection Association (USA):

Health: 1  
Flammability: 0  
Instability: 0

Date of Revision: May 31, 2012



# Material Safety Data Sheet

Pigment Ink                      TN-15                      Navy Blue

---

## 65. Product and Company Identification

Product Name:	Pigment Ink
Product Code:	TN-15
Company:	A Permanent Solution 1038 E. Bastanchury Road #186 Fullerton, CA 92835 USA www.apermanentsolution.com    E-mail: info@apermanentsolution.com Phone: (714) 441-1900              Fax: (714) 441-1808

---

## 66. Hazards Identification

Emergency Overview:	When involved in a fire or exposed to high temperatures for an extended period of time, organic pigments may smolder or burn evolving noxious fumes which can include oxides of nitrogen and carbon, or other toxic compounds.
---------------------	--

---

## 67. Composition/Information on Ingredients

Pigment Blue C.A.S # 147-14-8  
There are no additional ingredients which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

---

## 68. First Aid Measures

Eye Contact:	Remove contact lenses if present. Thoroughly flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact:	Wash skin with soap and water. Get medical attention if irritation develops.
Inhalation:	Move to fresh air. Get medical attention if irregular breathing occurs.

---

Pigment Ink                      TN-15                      Navy Blue                      1

---

Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
------------	--

---

## 69. Fire-Fighting Measures

Flammability of product:	Non-flammable organic pigment product.
Extinguishing Media:	Water fog
Special protective equipment for fire-fighters:	Self-contained breathing apparatus (SCBA) and full protective equipment recommended.

---

## 70. Accidental Release Measures

Small Spill:	For dry powder spills, inert materials such as sand may be added to control dusting prior to cleanup. Industrial grade vacuum sweepers are also recommended. Place spilled material into appropriate waste containers for disposal.
Large Spill:	Contain spilled material immediately with an inert substance such as sand or earth. Use plastic or aluminum shovel to transfer diluted waste material into appropriate containers for disposal.  Airborne organic pigment dust may be an explosion hazard. Secure possible sources of ignition and avoid dusting.

---

## 71. Handling and Storage

Handling:	Shut off all ignition sources. Wear appropriate protective clothing and equipment during clean-up. Contain the spill or leak. Place in a closable container for disposal.
Storage:	Store in a moderately cool, dry, well-ventilated area away from direct sources of heat. Empty containers may contain product residues and should be handled appropriately. Position containers so that any labeling information is visible.

---

## 72. Exposure Controls/Personal Protection

Engineering Measures:	The use of local exhaust ventilation is recommended.
Personal Protection:	NIOSH approved dust respirators are recommended when handling in areas of pigment dusting. Safety glasses are also recommended. Impervious

---

Pigment Ink	TN-15	Navy Blue	2
-------------	-------	-----------	---

---

clothing should be worn when gross contact is likely, such as when cleaning up spills of large amounts.

Exposure Limits:	Nuisance Dust (Total Dust):	OSHA PEL 15 mg/m <sup>3</sup>	ACGIH TLV 10 mg/m <sup>3</sup>
	Respirable Dust:	OSHA PEL 5 mg/m <sup>3</sup>	ACGIH TLV 5 mg/m <sup>3</sup>

---

### 73. Physical and Chemical Properties

Physical State:	Solid
Appearance:	Blue Powder

---

### 74. Stability and Reactivity

Stability:	The product is stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.
Hazardous Decomposition Products:	When involved in a fire, burning organic pigments may evolve noxious gases which are toxic. These compounds may include CO, CO <sub>2</sub> , NO <sub>x</sub>

---

### 75. Toxicological Information

General:	Bases upon industry-wide experience over many years of manufacturing and published toxicological studies, organic pigments in general are considered to be practically non-toxic. This low order of toxicity is probably due to the fact that pigments are somewhat inert and insoluble substances.  Skin and eyes contact may cause irritation. Ingestion may result in gastric disturbance. Dust inhalation may cause irritation of mucous membranes. Chronic effects of overexposure have not been established.
Acute Toxicity:	No known published data available.
Chronic Toxicity:	No known published data available.
Mutagenicity:	No known published data available.

---

### 76. Ecological Information

This product has not been evaluated for its ecotoxicity. However, the biodegradation of organic colorants under aerobic conditions is expected to be poor and there is no evidence to suggest they create any significant ecological

Pigment Ink	TN-15	Navy Blue	3
-------------	-------	-----------	---

---

problems when released into the environment. Since organic pigments are generally insoluble compounds, they are believed to have minimal bioaccumulation and bioavailability characteristics.

---

### 77. Disposal Considerations

**Waste Disposal:**

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

---

## **78. Transport Information**

**DOT Classification:**

Refer to the bill of lading for proper shipping information.

---

## **79. Regulatory Information**

**OSHA/HCS Status:**

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

**WHMIS (Canada):**

Not controlled under WHMIS (Canada).

**Europe:**

This product is not classified according to EU legislation.

---

## **80. Other Information**

**Date of Revision:**

February 14, 1996



# Material Safety Data Sheet

Pigment Ink

TN-28

Navel Orange

---

## 81. Product and Company Identification

Product Name:	Pigment Ink
Product Code:	TN-28
Company:	A Permanent Solution 1038 E. Bastanchury Road #186 Fullerton, CA 92835 USA www.apermanentsolution.com E-mail: info@apermanentsolution.com Phone: (714) 441-1900 Fax: (714) 441-1808

## 82. Hazards Identification

Emergency Overview:	When involved in a fire or exposed to high temperatures for an extended period of time, organic pigments may smolder or burn evolving noxious fumes which can include oxides of nitrogen and carbon, or other toxic compounds.
---------------------	--

---

## 83. Composition/Information on Ingredients

Pigment Orange 13 C.A.S # 3520-72-7  
This product is not considered to be a hazardous substance as defined under OSHA's Hazard Communication Standard (29 CFR 1910.1200).

---

## 84. First Aid Measures

Eye Contact:	Remove contact lenses if present. Thoroughly flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact:	Wash skin with soap and water. Get medical attention if irritation develops.
Inhalation:	Move to fresh air. Get medical attention if irregular breathing occurs.
Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Pigment Ink

TN-28

Navel Orange

1

---

## 85. Fire-Fighting Measures

Flammability of product:	Non-flammable organic pigment product.
Fire-Fighting media and Instructions:	Carbon dioxide, dry chemical or foam recommended. Apply water spray to cool exposed closed containers.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus (SCBA) and full protective equipment recommended.
Unusual fire and explosion hazards:	Fire or excessive heat may produce hazardous decomposition products.
General Hazard:	Improper handling of any finely divided organic pigment powder may lead to dust cloud formation which may be an explosion hazard.
NFPA Ratings:	Health: 1      Flammability: 1      Reactivity: 0
HMIS Ratings:	Health: 1      Flammability: 1      Reactivity: 0

---

## 86. Accidental Release Measures

Small Spill:	For dry powder spills, inert materials such as sand may be added to control dusting prior to cleanup. Industrial grade vacuum sweepers are also recommended. Place spilled material into appropriate waste containers for disposal.
Large Spill:	Contain spilled material immediately with an inert substance such as sand or earth. Use plastic or aluminum shovel to transfer diluted waste material into appropriate containers for disposal.  Airborne organic pigment dust may be an explosion hazard. Secure possible sources of ignition and avoid dusting.

---

## 87. Handling and Storage

Handling:	Avoid employee exposure through the use of appropriate engineering controls and good industrial hygiene practices.
Storage:	Store in a moderately cool, dry, well-ventilated area away from direct sources of heat. Empty containers may contain product residues and should be handled appropriately. Position containers so that any labeling information is visible.

---

## 88. Exposure Controls/Personal Protection

Engineering Measures:	The use of local exhaust ventilation is recommended.
Personal Protection:	NIOSH approved dust respirators are recommended when handling in areas

---

Pigment Ink	TN-28	Navel Orange	2
-------------	-------	--------------	---

---

Exposure Limits:	of pigment dusting. Safety glasses are also recommended. Impervious clothing should be worn when gross contact is likely, such as when cleaning up spills of large amounts. There are no ACGIH TLV's or OSHA PEL's established for this product.
------------------	---

---

## 89. Physical and Chemical Properties

Physical State:	Solid
Appearance:	Reddish Orange Powder
Melting Point:	320°C - 330°C

---

## 90. Stability and Reactivity

Stability:	The product is stable.
Hazardous Polymerization:	Hazardous polymerization will not occur.
Incompatibility:	Avoid strong oxidizing agents such as peroxides, chlorates, perchlorates, nitrates, and permanganates. Oxidizing materials may vigorously evolve oxygen in large amounts.
Hazardous Decomposition Products:	When involved in a fire, burning organic pigments may evolve noxious gases which are toxic. These compounds may include carbon monoxide, carbon dioxide, nitrous oxides, or hydrogen chlorides, depending on the pigment type.

---

## 91. Toxicological Information

General:	Bases upon industry-wide experience over many years of manufacturing and published toxicological studies, organic pigments in general are considered to be practically non-toxic. This low order of toxicity is probably due to the fact that pigments are somewhat inert and insoluble substances.
Acute Toxicity:	This product has a reported acute oral LD <sub>50</sub> value of 5 gm/kg or greater in rats. No irritation observed in cutaneous and mucosal tolerability.
Chronic Toxicity:	No damage to animals observed in unpublished sub-chronic feeding studies in rats.
Mutagenicity:	In vitro screening tests for mutagenicity had reported negative results in Ames Salmonella culture with DMSO solutions or dispersions of commercial pigments.

---

## 92. Ecological Information

This product has not been evaluated for its ecotoxicity. However, the biodegradation of organic colorants under aerobic conditions is expected to be poor and there is no evidence to suggest they create any significant ecological

problems when released into the environment. Since organic pigments are generally insoluble compounds, they are believed to have minimal bioaccumulation and bioavailability characteristics.

---

### 93. Disposal Considerations

Waste Disposal:

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

---

### 94. Transport Information

DOT Classification:

Refer to the bill of lading for proper shipping information.

---

### 95. Regulatory Information

OSHA/HCS Status:

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

WHMIS (Canada):

Not controlled under WHMIS (Canada).

Europe:

This product is not classified according to EU legislation.

---

### 96. Other Information

Date of Revision:

May 31, 1996